DATA SHEET



IP-SOLID *SC BULKHEAD ADAPTER*



The IP-Solid SC Series is a robust fiber optic interconnect solution designed for deployment in challenging environments that may include harsh temperatures, moisture, dust, and more. The IP-Solid SC Bulkhead Adapter is optimized for FTTH deployment with its IP68 rated light-weight plastic body.

The IP-Solid SC Bulkhead Adapter has the HFOA interface that accepts IP-Solid SC Male connector or most HFOC (Hardened Fiber Optic Connector). It perfectly works for panel mount application including boxes, terminals and closures.

FEATURES

- IP68 rated bulkhead adapter
- Plastic robust body
- UV resistance for outdoor applications
- Intermateable with HFOC style connectivity

APPLICATIONS

- FTTH
- Multiport terminals
- Splice closures

KEY BENEFITS



Mechanical Data

	Value
Durability	50 matings
Port Count	1 port (1 fiber)

Optical Data

	Value
Typical Insertion Loss (dB)*	0.10
Max. Insertion Loss (dB)*	0.20

* Based on master grade jumper to low loss random mating test

Environmental Data

	Value
IP Rating [*]	IP68
Operating Temperature (C)	-40°C to +75°C
UV Resistance	Yes
RoHS Compliance	2015/863 RoHS
REACH Compliance	Yes

* The IP rating was validated using a SENKO sourced cable and termination procedure. It is recommended to retest IP rating for any other cable types.

AST-IPSD-02 ORDER CODE example

Adapter Drawing





AST-IPSD-02 IP-Solid Bulkhead Adapter Panel Nut Tool

IP-Solid Bulkhead Adapter Panel Nut Tool





senko.com/contact

sales@senko.com 1-858-623-3300

DS-IP-000012-RevA-EN