DATA SHEET

LC *PREMIUM ADAPTER*

One Piece Design SC Footprint Compatible 988 Series C Premium Adapter with Inner Shutter

The SENKO LC Premium Adapter, the perfect complement to the SENKO LC Premium Connector. Engineered with a robust body design, this adapter not only meets but exceeds the rigorous GR-326-Core requirements, ensuring unparalleled performance. Its superior side loading capability outperforms standard design ultrasonically welded two-piece designs, offering enhanced reliability. For those concerned with safety, the optional laser shutter is a game-changer, providing -33 dB protection at 1310 nm and safeguarding users from harmful laser radiation. Available in both quad and duplex versions, the SENKO LC Premium Adapter is designed to fit the standard SC footprint without any rattle, thanks to its secure mounting clip. Whether it's for a high-stakes environment where safety and performance are critical, or for everyday use, this adapter is built to deliver exceptional durability and protection. Make the smart choice for your fiber optic network with the SENKO LC Premium Adapter.

FEATURES

- Robust body design ensures durability and longevity
- Exceeds GR-326-Core requirements to guarantees high performance beyond industry standards
- Increased side loading capability: provides better performance compared to standard ultrasonically welded two-piece designs
- Optional laser shutter offers safety with -33 dB protection at 1310 nm against laser radiation
- Quad and duplex versions available
- Standard SC footprint compatibility to ensures a perfect fit without rattle, enhancing stability

APPLICATIONS

- Telecommunications
- Data centers
- Local area networks (LANs)
- Fiber to the nome (FTTH)
- Enterprise networks
- Medical equipment
- Industrial applications
- Military and aerospace
- Broadcasting

KEY BENEFITS

- SC footprint compatability
- Enhanced reliability
- ✓ Unparalleled safety
- Exceptional durability
- Versatile applications

LC PREMIUM ADAPTER DATSHEET

Mechanical Data

	Value
Durability	200 matings per GR-326-Core
Fixing Method	Snap fit (adapter without flange) or screw and nut (adapter with flange)
Housing Material	Plastic
Alignment Sleeve Material	Zirconia
Dust Protection Method	Removable dust plugs
Fiber Count	Duplex or quad (2 or 4 channel)
Adapter Design	One piece (weldless flange)

Optical Data

	Value
Typical Insertion Loss (dB)*	0.10
Max. Insertion Loss (dB)*	0.20

* Based on master grade jumper to low loss random mating test

Environmental Data

	Value
Operating Temperature	-40°C to +75°C
RoHS Compliance	Yes
REACH Compliance	Yes
Humidity Resistance	95%

Adapter Duplex Drawing



2. Duplex and Quad No Shutter shown other options are available upon request.

3. Specifications subject to change without notice.

Adapter Quad Drawing





LC PREMIUM ADAPTER DATSHEET

Accessories - Production/Cleaning



Accessories - Interferometry

SUMIX Manta W+ Inspection Scope PN: SMX-Manta-W+





- Inspects 12 fiber in 2.6 seconds, 24 fiber in 4.5 seconds
- 0.5µm defect detection
- Inspection tips for MPO, CS, SN, LC available



- Inspects 12 fiber in 2.6 seconds, 24 fiber in 4.5 seconds
- 0.5µm defect detection





senko.com/contact

sales@senko.com 1-858-623-3300

DS-LC-000010-RevA-EN