

XP Fit Plus®

**FIELD INSTALLABLE
CONNECTOR**

**Easy
Installation in
Under 2 Minutes**

XP Fit Plus.LC


XP Fit Plus.SC

The SENKO XP Fit Plus® is a pre-polished, pre-assembled connector compatible with standard SC and LC connectors. No epoxy is required as an internal mechanical grip effectively holds the fiber in place and can be installed in under two minutes.


No epoxy or polishing



► 1 Cutting Fiber



► 2 Inserting Fiber



► 3 Take Out Connector



Complete XP-Fit Installation Kit


FEATURES

- Mechanical splice (index matching gel)
- Highly stable & reliable
- Perfect performance
- Compact package
- RoHS compliant
- Finished connector meets UL94-V0 flammability rated
- TIA/EIA 568-C.3 compliant

XP Fit Plus® CONNECTOR

QUALITY CONSTRUCTION

Without polishing or adhesives, SENKO's XP Fit Plus® makes on-site installations quick and easy, diminishing the need for epoxy curing and hand polishing at the work site. The XP Fit Plus® comes with an assembly jig and fiber holder for 250µm and 900µm tight buffered fiber, ensuring accurate alignment and fiber cleave when terminating. High quality index matching gel that will last the lifespan of the network.



Accurate Alignment and Fiber Cleave



Cable/Cord Coated Fiber

The XP-Fit can accept numerous cable sizes and cable types, making it the number one choice for flexibility and adaptability



Assembly in 2 Minutes

The XP-Fit can be assembled in under 2 minutes without special tools and with limited user experience

Size Comparison

