

SENKO's MPO-PLUS® stackable adapters are ideal for high-density applications using MPO connectors. They are available in 90- and 45-degree options to assist with fiber management in densely populated panels. Optional internal shutter gives added protection from harmful laser radiation on active ports.

The unique interlocking design allows for customization of port configurations, giving more flexibility with the design and size constraints of the mounting panel. Adapters can be assembled by the user with assembly fixture, or they can be pre-assembled to user configuration.

FEATURES

- 90° and 45° degree mounting options
- Configurable port count
- Center and offset keyways
- One piece outer body construction
- · Laser shutter option

APPLICATIONS

- Artificial intelligence (AI)
- FTT:
- Telecommunications
- Data center
- Cloud computing
- High performance computing (HPC)

KEY BENEFITS

- **✓** Customizable panel layout
- **✓** Angled mounting for cable routing
- Eye safety


Mechanical Data

	Value
Durability	500 matings per TIA-568.3
Fixing Method	Snap-fit or screw and nut (adapter with flange)
Housing Material Type	Plastic


Environmental Data


	Value
Operating Temperature	-40°C to +75°C
RoHS Compliance	Yes
REACH Compliance	Yes

Adapter Drawing - 780-1x MPO Stackable 90 Degree



Adapter Drawing - 780-2x MPO Stackable 45 Degree





Accessories - Cleaning



Accessories - Interferometry





- Inspects 12 fiber in 2.6 seconds, 24 fiber in 4.5 seconds
- 0.5µm defect detection
- Inspection tips for MPO, CS, SN, LC available

SMX Manta W+ MPO Polarity and Continuity Module



- Works for 8, 12, 24, 48 and 16, 32 fiber MPO
- · Auto test and analysis

SUMIX Max QM+ Inspection Scope PN: MAX-Ouantum



- Inspects 12 fiber in 2.6 seconds, 24 fiber in 4.5 seconds
- 0.5µm defect detection

SMX Manta W+ Benchtop Holder







sales@senko.com 1-858-623-3300 senko.com/contact