



**MPO<sup>PLUS</sup>  
Premium Mini  
Connector**

**MPO<sup>PLUS</sup>  
Standard  
Connector**

**MPO<sup>PLUS</sup>  
Bayonet  
Connector**

**MPO<sup>PLUS</sup>  
Latch  
Connector**

**MPO<sup>PLUS</sup>  
Micro Latch  
Connector**

**TYPE OF FERRULE**

|                              | MPO <sup>PLUS</sup><br>Premium Mini<br>Connector | MPO <sup>PLUS</sup><br>Standard<br>Connector | MPO <sup>PLUS</sup><br>Bayonet<br>Connector | MPO <sup>PLUS</sup><br>Latch<br>Connector | MPO <sup>PLUS</sup><br>Micro Latch<br>Connector |
|------------------------------|--|--|---|---|---|
| 12 Fiber SM and MM Standard  | ○  | ○  | ○   | ○   | ○   |
| 12 Fiber SM and MM Low Loss  | ○  | ○  | ○   | ○   | ○   |
| 24 Fiber SM and MM Standard  | ○  | ○  | ○   | ○   |   |
| 24 Fiber MM Low Loss         | ○  | ○  | ○   | ○   |   |
| 16 Fiber MM Standard         | ○  | ○  | ○   |   |   |
| 16 Fiber SM and MM Low Loss* | ○  | ○  | ○   |   |   |
| 32 Fiber MM Standard         | ○  | ○  | ○   |   |   |

**PIN TYPE**

|                       | MPO <sup>PLUS</sup><br>Premium Mini<br>Connector | MPO <sup>PLUS</sup><br>Standard<br>Connector | MPO <sup>PLUS</sup><br>Bayonet<br>Connector | MPO <sup>PLUS</sup><br>Latch<br>Connector | MPO <sup>PLUS</sup><br>Micro Latch<br>Connector |
|-----------------------|--|--|---|---|---|
| Gender Changeable Pin | ○  |  |   | ○   |   |
| MM Standard Pin       | ○  | ○  | ○   | ○   | ○   |
| SM Standard Pin       | ○  | ○  | ○   | ○   | ○   |
| MM Low Loss Pin       | ○  | ○  | ○   | ○   | ○   |
| SM Low Loss Pin       | ○  | ○  | ○   | ○   | ○   |

**BOOT SELECTION**

|                       | MPO <sup>PLUS</sup><br>Premium Mini<br>Connector | MPO <sup>PLUS</sup><br>Standard<br>Connector | MPO <sup>PLUS</sup><br>Bayonet<br>Connector | MPO <sup>PLUS</sup><br>Latch<br>Connector | MPO <sup>PLUS</sup><br>Micro Latch<br>Connector |
|-----------------------|--|--|---|---|---|
| Flat Ribbon Cable     |  | ○  |   |   |   |
| Ribbon Fiber Short    |  | ○  |   |   |   |
| Ribbon Fiber          | ○  | ○  |   | ○   |   |
| 2mm Round             | ○  | ○  |   | ○   |   |
| 2mm Round No Crimp    | ○  | ○  |   | ○   |   |
| 3mm Short             | ○  |  |   | ○   |   |
| 3mm Round             | ○  | ○  |   | ○   |   |
| 3mm Flex Angle        | ○  | ○  |   | ○   |   |
| 3.6mm Short           | ○  | ○  |   |   |   |
| 3.6mm Round           | ○  | ○  |   | ○   |   |
| 3.6mm Flex Angle Boot | ○  | ○  |   | ○   |   |
| 4mm Round             | ○  | ○  |   | ○   |   |
| 4.5mm Round           | ○  | ○  |   | ○   |   |
| 5mm Round             | ○  | ○  |   | ○   |   |
| 5.5mm Round           | ○  | ○  |   | ○   |   |

**ADDITIONAL FEATURES**

|                                       | MPO <sup>PLUS</sup><br>Premium Mini<br>Connector | MPO <sup>PLUS</sup><br>Standard<br>Connector | MPO <sup>PLUS</sup><br>Bayonet<br>Connector | MPO <sup>PLUS</sup><br>Latch<br>Connector | MPO <sup>PLUS</sup><br>Micro Latch<br>Connector |
|---------------------------------------|--|--|---|---|---|
| GR-1435 Qualified**                   | ○  |  |   |   |   |
| Reverse Polarity Housing***           | ○  |  |   |   |   |
| Free Floating Ferrule                 | ○  | ○  | ○   | ○   |   |
| Removable Housing                     | ○  | ○  | ○   | ○   |   |
| Oval Spring                           | ○  | ○  | ○   | ○   |   |
| 20N Spring for 16, 24, and 32 Ferrule | ○  | ○  | ○   | ○   |   |
| High Density Pull Tab                 | ○  |  |   |   |   |
| Enhanced Crimp Ring for Round Cable   | ○  | ○  |   | ○   |   |

\*Note: 16F MM Low Loss is for APC polish

\*\*Note: SM 12 fiber with A1 boot code and metal insert back post

\*\*\*Note: MM 12/24F flat polish only