


LC KEYED

CONNECTOR & ADAPTER

Manage multiple networks with reduced risks

MATED PAIRS
Each LC Keyed connector will mate only with same color LC adapter



Network Security

The Senko LC Keyed system offers mechanical network security for organizations desiring to segregate networks due to privacy or security concerns.

LC KEYED CONNECTOR	SINGLEMODE UPC	MULTIMODE
Typical Insertion Loss	0.08 dB	0.10 dB
Return Loss	≥ 55 dB	
Durability	<0.20 dB typical change, 500 matings	
Operating Temperature	-40°C ~ +75°C	
Ferrule Hole Sizes	125 μm +1/-0 Concentricity: ≤ 1 μm	127 μm

LC KEYED ADAPTER	
Insertion Loss	< 0.2 dB (zirconia sleeve)
Sleeve / Ferrule Withdrawal Force	1.0 N ~ 2.5 N (100gf ~ 250gf)
Durability	200 times as per GR-326-Core
Operating Temperature	-40°C ~ +85°C
Storage Temperature	-40°C ~ +85°C non-condensing

FEATURES

- LC Keyed connectors and adapters prevent improper connection of separate networks with common access points
- Twelve color-coded keyed combinations prevent improper access to networks
- Fast and easy network identification
- Each LC Keyed connector will mate only with same-color LC Keyed adapter
- LC Keyed connectors will not mate with standard LC adapters